SAFETY DATA SHEET

UNIQUE NAILS FIBER GEL

Prepared to OSHA, ANSI, NOHSC, WHMIS, 1002/58 & 1272/2008/EC Standards

SDS Revision: 5.3

SDS Revision Date: 11/28/2016

	1. PRODUCT INDENTIFICATION
1.1	Product Name:
	UNIQUE NAILS Fiber Gel Classic Line
1.2	Chemical Name:
	POLYURETHANE (METH)ACRYLATE PREPOLYMER RESIN BLEND
1.3	Synonyms:
	NA
1.4	Trade Names:
	FIBER, PINK FIBER, NATURAL PINK FIBER, COSMETIC PINK FIBER
1.5	Product Use:
	PROFESSIONAL USE ONLY
1.6	Manufacturer's Name:
	Angelina Iosifidou UNIQUE NAILS
1.7	Manufacturer's Adress:
	Ipsountos 7, 12132, Athens, Greece
1.8	Emergency Phone:
	+302107793777
1.9	Business Phone / Fax:
	+302108656070

2. HAZARD INDENTIFICATION

2.1 Hazard Identification:

WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. CAUSES EYE IRRITATION. Hazard Statements (H):H317 - May cause an allergic skin reaction. H320 - Causes eye irritation. Precautionary Statements (P): P261 - Avoid breathing fumes/gas/vapors/spray. P272 - Contaiminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves. P302 + P352 - IF ON SKIN - wash with soap and warm water. P305 + P351 + P338 - IF IN EYES - Rince continually with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing. P333 + P313 - If skin reaction or a rash occurs, get medical attention. P337 + P313 - ilf eye irritation persists, P321 - for specific first aid treatment (see section 4 of this Safety Data Sheet). P363 - Wash contaminated clothing before resuse. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDE).



2.2 Routes of Entry: Inhalation: YES Absorption: YES Ingestion: YES

2.3 Effects of Exposure:

INGESTION: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervouse system depression.

EYES & SKIN: The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye

inflamation, ulceration. The vapor is discomforting to the eye. Splashes may cause severe eye irritation, possible corneal burns and eye damage. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to the skin, especially after prolonged contact. The product can cause allergic skin

reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated expsoure.

INHALATION: Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system.

Symptoms of overexposure can include coughing, wheezing, nasal congestion and difficulty breathing. Inhalation of concentrated vaors can cause central nervous system depression (e.g., drowsiness, headaches, nausea). Odor may give

some warning of exposure but odor fatigue may occur.

2.4 Symptoms of Overexposure:

Symptoms of skin overexposure may include redness, itiching and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, deratitis) upon prolonged or repeated exposure.

2.5 Acute Health Effects:

Moderate irritation to eyes near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.

2.6 Chronic Health Effects:

The material may cause an allergic reaction for some sensitive individuals.

2.7 Target Organs:

Eves, skin

		3. COMPO	SITION &	INGRED	IENT	INFO	RMA	TION					
					EXPC	SURE I	LIMITS	IN AIR	(mg/m	3)			
					A(CGIH		NOHS	С		OSHA	4	
					р	pm		ppm	1		ppm	1	4
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
Bis-HEA Poly(1,4-	NA	NA	NA	20-60	NA	NA	NA	NF	NF	NA	NA	NE	-
butanediol)-9 / IPDI					•			•		•			
Copolymer													
Bis-Hydroxyethyl	NA	NA	NA	20-60	NA	NA	NF	NF	NF	NA	NA	NA	
Methacrylate		-	•	•	<u>.</u>	_ <u>.</u>	-	-	-	<u>-</u>	-	- -	-
Poly(neopentyl Glycol													
Adipate)/IPDI													
Copolymer Dilution													
Trimethylpropane	3290-92-4	NA	NA	5-20	NA	NA	NF	NF	NF	NA	NA	NA	
trimethacrylate													
Tripropyleneglycol	42978-66-5	NA	Ina	5-20	NA	NA	NF	NF	NF	NA	NA	NA	
diacrylate													•
Silica	67762-90-7	NA	204-337-6	1-8	NA	NA	NF	NF	NF	NA	NA	NA	
		1	_				1	T					1
1-Hydroxycyclohexyl	947-19-3	NA	213-426-9	0.1 - 5	NA	NA	NF	NF	NF	NA	NA	NA	
phenyl ketone							-				-	_	
bis-trimethylbenzoyl	162-881-26-7	NA	423-340-5	≤1.0	NA	NA	NF	NF	NF	NA	NA	NA	
phenyl phosphine	Skin Sens. 1; Aqu	uatic Chronic 4	; H317, H413										
oxide MAY ALSO CONTAIN:													
CI 77891 (Titanium	13463-67-7	XR2275000	236-675-5	≤1.0	NA	NA	NF	NF	NF	NA	NA	NA	
Dioxide)			-	-			-	-	-	-	-	-	-
CI 15850 (Red 6)	17852-98-1	NA	241-806-4	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	
		-	-	•	•		•	•			-		-
CI 47005 (Yellow 10))	8004-92-0	NA	305-897-5	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77491 (Iron Oxides)	1309-37-1	NO742000	0 215-168-2	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	
(
CI77499 (Iron Oxides)	12227-89-3	NA	215-277-5	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	
** Due to trade	L secret information	more detailed	d concentratio	ns of the in	gredier	nts can	not he	nrovid	ed				
Due to trade :	, corec in ormation	.,ore actualet						p. 5 v iu					
			4. FIRST	AID MI	:ASU	IKES							
4.1 First Aid:	If in goods of allow		aisimal If mundin		المستوال	اد مسما	. دا مىلىداد	بسمام	a f at		a:11, 18.4	NACDIA:	TELV 16 +6 a
INGESTION:	If ingested, do n patient is vomiti							-					
	nearest Poison	_			_								
	ingested and the						u cs.	·······································	oc				nace iai vias
SKIN & EYES:	If product gets in						ı wateı	for at	least 1	5 min	utes.	Open a	nd close
	eyelid(s) to ens	•										•	
	attention. If irrit	_	_						-				
	washing of the a		-			_	-					-	_
	wash thoroughl	v hoforo rous	o If irritation	rodnoss or	con allin	na narc	icte co	neult	a nhvsi	ician ir	nmedi	atoly	

INHALATION: Remove victim to fresh air at once. If breathing stops, perform artificial respiration. Seek immediate medical attention.

Pre-existing dermatitis, other skin conditions and disorders of the target organs (eyes, skin) FLAMMABILITY

HEALTH

EYES SKIN

PHYSICAL HAZARDS

PROTECTIVE EQUIPMENT

0

0

4.2 Medical Conditions Aggravated by Exposure:

	5. FIREFIGHTING MEASURES	3 of
	Flashpoint & Method:	
	>100 °C (>212 T)	
5.2	Autoignition Temperature:	
	NA .	
5.3	Flammability Limits: Lower Explosive Limit (LEL): NA Upper Explosive Limit (UEL): NA	
5.4	Fire & Explosion Hazards:	
	When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO, CO2 and Nox)	
5.5	Extinguishing Methods:	
	Water, Foam, CO2, Dry Chemical	
5.6	Fire Fighting Procedures:	
	First responders should wear eye protection. Structural fire fighters must wear full protective equipment and	
	MSHA/NIOSH approved, self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains,	
	bodies of water or other enviormentally sensitive reas. If necessary, rinse contaminated equipment with soapy water	
	hefore returnign to service.	
	6. ACCIDENTAL RELEASE MEASURES	

6.1 Spills:

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., , 1 gallon [3.785 liters]) wear appropriate personal protective equipment (e.g., goggles & gloves). Maximize ventilation (open doors and windows). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. For large spills (e.g., > 1 gallon [3.785 liters]) deny entery to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

7. HANDLING AND STORAGE INFORMATION

7.1 Work & Hygiene Practices:

Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty of soap and water after using this product. If necessary, use a moisturizer after washing. Do not eat, drink or smoke while handling this product.

7.2 Storage & Handling:

Use and store in a cool, dry, well ventilated location. Keep away from excessive heat. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devises. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers shoiuld be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. KEEP AWAY FROM CHILDREN AT ALL TIMES!

Special Precautions:

Do not store where temperatures can exceed 50 $^{\circ}$ C (122 $^{\circ}$ L).

8.1 Ventilation & Engineering Controls: Use with adequate ventilation (e.g., local exhaust ventilation, fans). Ensure appropriate decomposition (e.g., sink, safety shower, eye wash station).					
8.2	Respiratory Protection:	No special respiratory protections is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR § 1910.134, application U.S. State regulations or the Candaian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC Member States or Australia.			
8.3	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side shields) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.			
8.4	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., >1 gallon [3.785 liters]), wear nitrile or imprevious gloves.	ELL		
8.5	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., . 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.			
		9. PHYSICAL & CHEMICAL PROPERTIES			
9.1	Density:	1.1			
9.2	Boiling Point:	NA			
9.3	Melting Point:	ND			
9.4	Evaporation Rate:	NA			
9.5	Vapor Pressure:	ND			
9.6	Molecular Weight:	NE			
9.7	Appearance & Color:	Clear or pigmented liquid			
9.8	Odor Threashold:	NE			
9.9	Solubility:	Not soluble			
9.1	pH:	NA .			
.11	Viscosity:	approximately 65,000 cps			
.12	Other Information:	NA .			
		10. STABILITY & REACTIVITY			

	10. STADIETT & REACTIVITY
10.1	Stability:
	Relatively stable under ambient conditions when stored properly.
10.2	Hazardous Decomposition Products:
	If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of
	carbon and nitrogen).
10.3	Hazardous Polymerization:
	Will not occur.
10.4	Conditions to Avoid:
	Exposure or contact to extreme temperatures, incompatable chemicals, strong light sources, sparks and flame.
10.5	Incompatable Substances:
	Strong oxidizers, peroxides, strong acids or alkalis.

14.5 ADR/RID (EU):

NOT REGULATED

14.6 MEXICO (SCT):

NOT REGULATED

14.7 ADGR (AUS):

NOT REGULATED

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	ACGIH American Conference on Governmental Industrial Hygienists				
TLV	TLV Threshold Limit Value				
OSHA	OSHA U.S. Occupational Safety and Health Administration				
PEL Permissible Exposure Limit					
IDLH Immediately Dangerous to Life and Health					

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard				
1	1 Slight Hazard				
2	Moderate Hazard				
3	Severe Hazard				
4	Extreme Hazard				



PERSONAL PROTECTION RATINGS:

Α		
В		
С		
D		
E		
F		















Dust & Vapor Half-Mask Respirator

Full Face Respirator

a Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILIT	FLAMMABILITY LIMITS IN AIR:					
	Minimum temperature required to initiate combustion in air with no other					
Temperature	source of ignition					
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will					
	explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will					
	explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

0	Minimal Hazard		
1	Slight Hazard		
2	Moderate Hazard		
3	Severe Hazard		
4	Extreme Hazard		
ACD	Acidic		
ALK	Alkaline		
COR	Corrosive		
w	Use No Water		
ОХ	Oxidizer		
TREFOIL	Radioactive		



TOXICOLOGICAL INFORMATION:

Lethal Dose (solids & liquids) which kills 50% of the exposed animals
\$
Lethal concentration (gases) which kills 50% of the exposed animal
Concentration expressed in parts of material per million parts
Lowest dose to cause a symptom
Lowest concentration to cause a symptom
Lowest dose (or concentration) to cause lethal or toxic effects
International Agency for Research on Cancer
National Toxicology Program
Registry of Toxic Effects of Chemical Substances
Bioconcentration Factor
Median threshold limit
Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	IIS Canadian Workplace Hazardous Material Information System					
DOT	U.S. Department of Transportation					
TC	TC Transport Canada					
EPA	EPA U.S. Environmental Protection Agency					
DSL	DSL Canadian Domestic Substance List					
NDSL	Canadian Non-Domestic Substance List					
PSL	Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	EU European Union (European Union Directive 67/548/EEC)					
WGK	WGK Wassergefährdungsklassen (German Water Hazard Class)					

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(*)	(2)	②	①	®		(Ř
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

		**				×	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

		③	\Diamond			((1)
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment